



The IM-10 is specifically designed to mount to the front of an LDS Church sacrament table.

The microphone is intuitive and easy to mount. The IM-10's swing-down front panel activates the microphone. The design allows for silent activation and deactivation of the microphone, while the "shelf" created by swinging down the front panel is the ideal mounting place for the approved sacrament prayer card (LDS Distribution Center part # 35786).

When the front panel is lowered to the operating position (as depicted in the above illustration), an LED is visible on the exposed front surface of the microphone, which indicates the connection of the microphone to the mixer and the presence of Phantom™ Power.

The IM-10 is designed for new installations (a 1 inch hole must be drilled in the front of the sacrament table if no opening is present), or as a retrofit to an existing installation. The IM-10 will cover the hole of a previously installed, older sacrament microphone. A one-to-one (1:1) installation template is supplied with each microphone. Installation is simple and straightforward using the template and the four supplied mounting screws.

Specifications

Microphone type:	electret condenser
Output level:	commensurate with podium and hand mics in LDS chapel
Powering:	standard Phantom™ power
Activation (on/off)	lower front panel to place in operation
Dimensions:	3" H, 1.23" D, 10" L
Shipping weight	1 lb 9oz
Material:	18 ga. steel
Finish:	dark brown paint
Output connection:	output is standard 3-pin male XLR-type connector
Mounting:	4 screws (supplied) mount the IM-10 to a flat surface

Our new address
Ivie Technologies, Inc.
1605 NW State St.
Lehi UT 84043
Ph: 801-766-7600
Fax: 801-766-8282